



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		S125DL			
MATERIAL		HOUSING-ABS			
		LENS-AS			
		REFLECTOR-HEAT RESISTING ABS			
FLASHING PER MIN.		60 ~ 80			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
USE VOLT.	LED	CURRENT	DC12V	0.08W	MAX. 0.520A
			DC24V		
			AC110V		
			AC220V		0.065A
KIND OF SOUND		WS	5 Warning Sounds		
		WM	5 Melodie		
		WA	5 Alarms		
		WV	5 Customizable sounds		
VOLUME		MAX. 105dB at 1m			
PROTECTION GRADE		WATER & DUST PROOF IP54			
CABLE ENTRY		$\phi 10$ LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		LED STEADY/FLASHING LIGHT			

	ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH
	f	m	Ⓢ	v		
FOR LINEAR DIMENSIONS	0.5~3	±0.05	±0.1	±0.2	-	
	3~6			±0.3	±0.5	
	6~30	±0.1	±0.2	±0.5	±1	
	30~120	±0.15	±0.3	±0.8	±1.5	
	120~400	±0.2	±0.5	±1.2	±2.5	
	400~1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	
	10~50	±0°30'		±1°	±2°	
	50~120	±0°20'		±0°30'	±1°	
	120~400	±0°10'		±0°13'	±0°30'	

Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
S.H.KIM	J.H.PARK		J.K.HAN	3	2019.03.20	
TITLE			MODEL			
S125DL OUTLINE DRAWING			S125DL			
			DWG. NO.			
			S125DL_OUT			
SCALE	SIZE	REV	SHEET			
N/S	A4	00	1/1			