


| MARK | DATE | REVISION | REVISER | APP. BY |
|------|------|----------|---------|---------|
| ① | | | | |
| ② | | | | |
| ③ | | | | |

| | | | |
|------------------|-------------------------|--------|--------|
| MODEL NO | SM200 | | |
| MATERIAL | HOUSING-STEEL / AL | | |
| USE VOLT. | CURRENT | DC24V | 7.820A |
| | | AC110V | 2.105A |
| | | AC220V | 1.005A |
| VOLUME | MAX. 120dB | | |
| PROTECTION GRADE | WATER & DUST PROOF IP44 | | |
| CABLE ENTRY | Ø9 LEAD HOLE | | |
| COLOR | RED | | |
| RATING | 10 MIN. | | |

| ISO2768-1 : CLASS OF TOLERANCE | | | | | SURFACE FINISH |
|--------------------------------|---------|--------|------|--------|----------------|
| FOR LINEAR DIMENSIONS | | f | m | (C) | |
| | 0.5~3 | ±0.05 | ±0.1 | ±0.2 | - |
| | 3~6 | | | ±0.3 | ±0.5 |
| | 6~30 | ±0.1 | ±0.2 | ±0.5 | ±1 |
| | 30~120 | ±0.15 | ±0.3 | ±0.8 | ±1.5 |
| | 120~400 | ±0.2 | ±0.5 | ±1.2 | ±2.5 |
| 400~1000 | ±0.3 | ±0.8 | ±2 | ±4 | |
| FOR ANGULAR DIMENSIONS | | | | | |
| | 0~10 | ±1° | | ±1°30' | ±3° |
| | 10~50 | ±0°30' | | ±1° | ±2° |
| | 50~120 | ±0°20' | | ±0°30' | ±1° |
| | 120~400 | ±0°10' | | ±0°13' | ±0°30' |

| Nr. | DWG. NO. | TITLE/ NAME | MAT'L | QTY | REFERENCE |
|---|----------|-------------|-----------|------|------------|
| DSND BY | CHKD BY | CHKD BY | APRV BY | VIEW | DATE |
| S.H.KIM | J.H.PARK | | J.K.HAN | 3 | 2019.03.20 |
| TITLE | | | MODEL | | |
| SM200 OUTLINE DRAWING | | | SM200 | | |
|  | | | DWG. NO. | | |
| | | | SM200_OUT | | |
| SCALE | SIZE | REV | SHEET | | |
| N/S | A4 | 00 | 1/1 | | |

A4(297X210)