



MARK	DATE	REVISION	REVISER	APP .BY
△				
△				
△				

MODEL NO		S80AS		
MATERIAL		HOUSING-ABS		
		LENS-AS		
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()		
FLASHES PER MIN.		60 ~ 80		
USE VOLT.	XENON	CURRENT	DC12V	MAX. 0.433A
			DC24V	MAX. 0.216A
			AC110V	MAX. 0.076A
			AC220V	MAX. 0.061A
VOLUME		MAX. 90dB at 1m		
PROTECTION GRADE		WATER & DUST PROOF IP44		
CABLE ENTRY		Ø8 LEAD HOLE		
COLOR OF HOUSING		MAKER STANDARD		
ACTION		XENON LAMP STROBE LIGHT		

FOR LINEAR DIMENSIONS	ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH
	f	m	⊙	v		
0.5~3			±0.2	-		
3~6	±0.05	±0.1	±0.3	±0.5		
6~30	±0.1	±0.2	±0.5	±1		
30~120	±0.15	±0.3	±0.8	±1.5		
120~400	±0.2	±0.5	±1.2	±2.5		
400~1000	±0.3	±0.8	±2	±4		
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°		
	10~50	±0°30'	±1°	±2°		
	50~120	±0°20'	±0°30'	±1°		
	120~400	±0°10'	±0°13'	±0°30'		

Nr.	DWG. NO.	TITLE/ NAME	MAT'L	1	-
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
TITLE			MODEL		
S80AS OUTLINE DRAWING			S80AS		
			DWG. NO.		
			S80AS_OUT		
SCALE	SIZE	REV	SHEET		
N/S	A4	00	1/1		