



MARK	DATE	REVISION	REVISER	APP .BY
△				
△				
△				

MODEL NO		S80RK		
MATERIAL		HOUSING-ABS		
		LENS-AS		
		REFLECTOR-HEAT RESISTING ABS		
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()		
REV. PER MIN.		120 ~ 140		
USE VOLT.	BULB	CURRENT	DC12V	MAX. 0.484A
			DC24V	MAX. 0.310A
			AC110V	MAX. 0.080A
			AC220V	MAX. 0.040A
PROTECTION GRADE		WATER & DUST PROOF IP44		
CABLE ENTRY		$\phi 13$ LEAD HOLE		
COLOR OF HOUSING		MAKER STANDARD		
ACTION		BULB REVOLVING WARNING LIGHT		

FOR LINEAR DIMENSIONS	ISO2768-1 : CLASS OF TOLERANCE				
	f	m	Ⓞ	v	
0.5-3			±0.2	-	
3-6	±0.05	±0.1	±0.3	±0.5	
6-30	±0.1	±0.2	±0.5	±1	
30-120	±0.15	±0.3	±0.8	±1.5	
120-400	±0.2	±0.5	±1.2	±2.5	
400-1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0-10	±1°	±1°30'	±3°	
	10-50	±0°30'	±1°	±2°	
	50-120	±0°20'	±0°30'	±1°	
	120-400	±0°10'	±0°13'	±0°30'	

-		-		-		-		1		-	
Nr.	DWG. NO.	TITLE/ NAME			MAT'L	QTY	REFERENCE				
DSND BY	CHKD BY	CHKD BY		APRV BY	VIEW	DATE					
S.H.KIM	J.H.PARK			J.K.HAN	3	2016.08.30					
TITLE					MODEL						
S80RK OUTLINE DRAWING					S80RK						
					DWG. NO.		S80RK_OUT				
					SCALE	SIZE	REV	SHEET			
N/S		A4	00	1/1							